

# Construction

# Roc-Bloc™

## Bridge Debris Containment



### **Roc-Bloc™ Heavy Duty Debris Nets**

- InCord debris net systems can wrap a bridge into a cocoon for safety – protecting workers, pedestrians, underpass traffic and adjacent properties.
- Durable and reusable debris netting is available in single panel or stacked configurations under our brand name Roc-Bloc™ with various mesh size and strengths to meet your exact job requirements.
- InCord debris liners combined with 2-1/2 inch load bearing structural netting provides superior strength for applications requiring heavy debris containment.
- Our netting ensures unrestricted work site access and traffic flow. For bridge containment needs, DOT safety engineers and construction managers look to InCord for custom solutions.
- Roc-Bloc debris net systems are custom sized and fabricated to meet your project requirements.
- Debris nets and liners are available in a choice of three colors – black, gray, sand.
- Roc-Bloc™ safety netting complies with OSHA regulations for debris net installations and meets CPAI-84, Section 6, Tent Walls and Tops.
- Roc-Bloc™ meets conformity standard ANSI A10.37 for Debris Net Systems for Construction and Demolition.



### **Personnel Safety**

- InCord Roc-Bloc™ bridge safety netting can provide personnel fall protection and debris protection, all in one system when installed at a walking/working surface. (OSHA 1926.502).

# Roc-Bloc contains construction debris and spauling – protecting your workers and the public below.



Heavy duty structural nets offer fall protection for bridge construction workers while debris containment liners keep the traffic below safe from falling objects during times active construction.



12 cubic feet of concrete caught by safety netting with debris liner.



Hoover Dam Bypass Project US 93

N-820H black structural netting with WS70 black liner.

### Debris Net Specifications for N-820H

- Style: Raschel Knotless Netting
- Fiber ..... High Tenacity, Polypropylene (HTPP)
- Cord Diameter .... 3/16 inch (5 mm)
- Mesh Size..... 2-1/2 inch (60 mm) square opening
- Load Test, Max ... 6000 lb (2700 kg)
- Weight ..... 0.0528 lb/ft<sup>2</sup> (258 g/m<sup>2</sup>)
- Melting Point..... 320°F (160°C)
- UV..... Extra UV Stabilizers added
- Colors ..... Black, Gray, Sand



N-820H gray structural netting with DNR850 gray liner.

### Debris Liners



WS70BK  
1/8" Knitted Polyethylene  
Opacity 70 %



WS85SD  
1/16" Knitted Polyethylene  
Opacity 85 %



3/8" Knitted Polyester  
DNR900 Black • DNR850 Gray • DNR500 Sand

Roc-Bloc™ panels are layered and joined together at the border with 75 mm HTPP webbing and then double-stitched with polyester thread. Grommets are installed one foot on-center along all sides of the panel.



Call InCord for all your netting needs at 1-800-596-1066



InCord

226 Upton Road  
Colchester, CT 06415

Phone: 860-537-1414 • Fax: 860-537-7393  
www.InCord.com • netting@InCord.com



InCord is an ISO 9001 registered company  
CAGE Code No. 1NPR7

**INCORD**