

# Construction

## Scaffold & Debris Nets



Where there's construction, there's debris –falling or flying objects that can seriously injure people and severely damage property if not for the safeguard of protective netting.

Construction netting consisting of scaffold wind/sun block and vertical debris nets can wrap a building in safety, protecting workers, pedestrians, and nearby structures from harm of falling material.

InCord scaffold and debris netting, a standard in the industry, is available in small mesh size for wind and sun bloc to 1/4 inch heavy strength mesh. Debris netting may be used in a stacked configuration or used as a liner in combination with structural netting such as personnel safety nets.

Our scaffold and debris nets are ultra-durable, reusable, and can be moved from floor to floor. Our scaffold netting complies with OSHA regulations and meets CPAI-84, Section 6, Tent Walls and Tops.



We can provide you with in-stock netting or custom netting.



**Scaffold and Debris Nets improve productivity and reduces downtime from accidents and clean up.**



**Specifications and Sizes**

| Model                      | Material                  | Color              | Thickness inch | Weft holes/inch | Warp holes/inch   | Opacity                  | Ball Burst ASTM D3786    | Weight oz/sq yd | FR Rating       | Tarp Sizes  | Roll Goods  |
|----------------------------|---------------------------|--------------------|----------------|-----------------|---|--------------------------|--------------------------|-----------------|-----------------|---|---|
| RPY13AN                    | knit polyester            | white green        | 0.0475         | 9.75            | 11.75   | 85%                      | 500 lbf/in <sup>2</sup>  | 13.7            | no <sup>1</sup> | custom  | 8' 4" x 150'  |
| WS85                       | knit polyester            | sand               | 0.0325         | 9.75            | 11.75   | 85%                      | 209 lbf/in <sup>2</sup>  | 5.3             | no <sup>1</sup> | custom  | 6' x 150'   |
| WS70 BK HDPE               | high density polyethylene | black              | 0.0450         | 5.00            | 7.50  | 70%                      | 312 lbf/in <sup>2</sup>  | 5.1             | no              | custom  | max. width 16 ft (5 m)<br>max. length 164 ft (50 m) |
| WS70 WH<br>WS70 GN<br>HDPE | high density polyethylene | white green        | 0.0350         | 5.00            | 7.50  | 70%                      | >100 lbf/in <sup>2</sup> | 4.4             | no              | custom  | 8' x 150' wh, gn<br>8.5' x 150' wh<br>10' x 300' gn |
| WS70 PP                    | polypropylene             | black              | 0.0350         | 5.00            | 7.50  | 70%                      | 341 lbf/in <sup>2</sup>  | 6.4             | no              | PSN   | --  |
| WS70 FR                    | polyethylene              | black <sup>2</sup> | 0.0350         | 5.00            | 7.50  | 70%                      | 160 lbf/in <sup>2</sup>  | 4.4             | NFPA-701        | custom  | 8' x 150'<br>8' 6" x 150'                           |
| Model                      | Material                  | Color              | Thickness inch | Mesh Size       | Breaking Strength ASTM D5034<br>Warp (1 inch grab) Weft |                          | Weight oz/sq yd          | FR Rating       | Tarp Sizes      | Roll Goods  |   |
| DNR18                      | PVC coated polyester      | orange             | 0.0185         | 1/8 x 3/16 inch | 179 lbf/in <sup>2</sup>                                 | 94 lbf/in <sup>2</sup>   | 5.90                     | NFPA-701        | custom          | 4' x 150'<br>5' 6" x 150'                                 |   |
| DNR75                      | knit polyethylene         | black              | 0.035          | 5/16 inch       | 87.7 lbf/in <sup>2</sup>                                | 66.4 lbf/in <sup>2</sup> | 3.40                     | no              | custom          | 4' x 150'<br>8.5' x 150'<br>10' 6" x 150'                 |   |
| DNR75 FR                   | knit polyethylene         | orange blue        | 0035           | 5/16 inch       | 87.7 lbf/in <sup>2</sup>                                | 66.4 lbf/in <sup>2</sup> | 3.40                     | NFPA-701        | custom          | 4' x 150'<br>5' 6" x 150'<br>8.5' x 150'<br>10' 6" x 150' |   |
| Model                      | Material                  | Color <sup>3</sup> | Thickness inch | Mesh Size       | Breaking Strength ASTM D3787<br>Ball Burst              |                          | Weight oz/sq yd          | FR Rating       | Tarp Sizes      | Roll Goods  |   |
| RPY14WH                    | knit polyester            | white              | 0.043          | 1/4 inch        | 125 lbf/in <sup>2</sup>                                 |                          | 4.15                     | NFPA-701        | custom          | 10' x 300'  |   |
| RPY14BK                    | knit polyester            | black              | 0.043          | 1/4 inch        | 125 lbf/in <sup>2</sup>                                 |                          | 4.15                     | NFPA-701        | custom          | 10' x 300'  |   |

1. NFPA-701 version available on special order    2. Available Colors: black, white, green.    3. Std. Colors: sand, merlot, green, white, gray, black – custom colors available.

Debris liners are available in roll form with selvage edge with button holes or in tarp configurations with a web border and grommets. Please note that we specialize in custom netting, call for a quotation on other sizes.




RPY13AN




WS85



WS70



DNR18



DNR75



RPY14WH / RPY14BK

**Call InCord for all your netting needs at 1-800-596-1066**



**InCord**

226 Upton Road  
Colchester, CT 06415

Phone: 860-537-1414 • Fax: 860-537-7393  
incord.com • netting@incord.com



InCord is an ISO 9001 registered company  
CAGE Code No. 1NPR7

**INCORD**